# 

## 12-Channel PC ECG

custo cardio 300 | Resting and Stress ECG



### custo cardio 300

- Sampling rate up to 32kHz which gives higher resolution and improved pacemaker detection
- Interchangeable patient cables (banana, clip, connection to suction system possible) offering the highest levels of versatility
- Quality of the patient connection displayed directly on the device
- Start/stop-button for ECG recording directly on the device
- Operating time with rechargeable battery approx. 10h
- Available with rechargeable battery or battery (2 x AAA)
- Online-control for ECG recording (10 sec.) directly on the device
- Flexible connection with every PC (USB, BT/WIFI)
- Recording, viewing, analysing and reporting of a 12-channel ECG on every PC in the network
- Online analysis and display of events relating to heart rate and ventricular events during recording
- Easy and cost-efficient extension to CPET

Your authorised custo med dealer





	1000, 2000, 4000, 8000, 16000 (USB only), 32000 Hz (USB only)	Components for the ECG recording:	
Deviation	< 1.5%	· custo cardio 300	
A/D converter	24 Bit · neoprene pouch		
Input impedance	>10 M0hm	· belt · ECG electrodes	
Amplitude quantification	1,525 μV/bit		
CMRR	> 93 dB		
Defibrillation protection	Electrical potential 5000 V (recovery time $< 5$	< 5 s)	
Power supply	Lithium-polymer battery		
Energy consumption	max. 1.5 watt		
Connection to the PC*	USB (cable length 2.50 m)		
BT-range	max. 10 m, due to environmental conditions		
BT-frequency	2,4 GHz frequency band		
oftware, additional functions (custo diagnostic)	TRUE WAVE <sup>®</sup> , mains filter, muscle filter, ergo f pacemaker detection and verification	ilter,	
Dimesions	approx. 115 * 75 * 18 mm (L * W * H)		
Weight	approx. 140 g (version with rechargeable batte	ery)	
Patient leads	approx. 1050 mm (limb leads) approx. 700 mm (chest wall)	Channel • 12 Channel • movinty • 10 • moving • 50 •	
Classification Version: USB Version: USB/BT/W-LAN	Class IIa, Typ CF Protection Category II Device with internal power supply	75 102/2015 15:10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Applied standards	DIN EN 60601-1, 60601-1-2, 60601-2-25	ave ave ave	

#### custo diagnostic (software)

- Versatile connection possibilities into existing IT structures (HL7, FDA-XML, SQL, GDT, SCP)
- Comparison of all patients examinations
- Comfortable reports with predefined text modules
- Clearly arranged A4 paper printouts
- Paperless medical practice: Distribution of evaluations and reports as email, fax, PDF and as evaluation file (.cst)

#### Resting ECG software functions

- Single beat analysis, cumulative complexes, measurement table, interpretation
- Unconfirmed reporting

#### Stress ECG software functions

- Online arrhythmia detection with acoustic and visual warning function
- Predefined profiles with the possibility for customized configuration
- Control of treadmills, sitting and supine ergometers via software
- Automatic recording of blood pressure, SpO<sub>2</sub> and lactate
- Summary of all examination-specific values in a report

custo med GmbH • Maria-Merian-Str. 6 • 85521 Ottobrunn, Germany Phone: +49 (0)89 71098-00 • Fax: +49 (0)89 71098-10 Email: info@customed.de • Internet: www.customed.de



ST VS

▼ 50

150 100 50

150 100 50

0.1 0.0

0.2